



DD5/DD5M/TL5R自动脱帽离心机

DD5/DD5M/TL5R Automatic Uncovering Centrifuge



特性

- 整机设计符合人机工程学，流线型设计，更加安全美观实用。
- 微电脑控制，TFT真彩大屏幕触控液晶显示/数码显示，满足各种客户的要求。
- 采用全钢结构，不锈钢离心腔，坚固耐用。
- 采用无刷变频电机，免维护，无粉尘污染，运行宁静清洁。
- 10种升、降速率选择。
- 设有离心力显示专用键，运行中可随时更改参数，无需停机。
- 采用静音机电一体化电机门锁。
- 设有多重减震装置，具有自动平衡功能，运行平稳。
- 有多款适用于通用管、微孔板的水平转子和角转子供用户选择。
- 可存储20个运行程序

技术参数 Specifications

型号 Model	DD5 (脱帽) (Automatic Uncovering)	DD5M (脱帽) (Automatic Uncovering)	TL5R (脱帽) (Automatic Uncovering)
采血管分离数量 Blood tube splite quantity	48、76 tubes	124 tubes	124 tubes
最高转速 Max Speed (r/min)	4000	5000	5500
最大离心力 Max RCF (×g)	3780 × g	3780 × g	4800 × g
转速精度 Speed precision	± 50r/min		
制冷系统 Refrigeration system	进口无氟制冷压缩机组 (R404a) Import fluoride-free compressor and control valve (R404a)		
温控范围 Temp.control range	-20℃ ~ +40℃		
温控精度 Temp.precision	± 1℃		
控制及驱动系统 Control and drive system	交流变频电机，微机控制，直接驱动 Frequency motor, micro control, direct driver		
运行程序 Operation programe	20个sets		
定时范围 Time Range	0-99h59min		
电 源 Power	AC220V 50Hz		
噪 音 Noise	≤65dB (A)		
总功率 Weight	800w	1000w	2000w
外形尺寸 Dimensions (L × W × H)	630 × 500 × 420mm	710 × 560 × 770mm	710 × 560 × 770mm
重 量 Weight	50kg	75kg	150kg



Features

- The design of the whole machine is in line with the ergonomics, with streamlining sculpt,better looking and more efficient.
- Microcomputer-controlled,with a TFT true-color LCD widescreen touch monitor and digital indicator to meet different customers requirements.
- With a complete steel structure and a stainless steel centrifuge cavity, it is sturdy and durable.
- Variable-frequency brushless motor that is maintenance and dust-free to achieve quite and clean operation
- 10 levels for speed-up and speed-down control.
- With a motor gate lock mute mechanical & electrical integration.
- Can store 20 user programmes.

可选配件 Optional fittings



48 × 7/5ml



76 × 7/5ml



124 × 7/5ml