

HR26M高速冷冻离心机

HR26M High-speed Refrigerated Centrifuge

特性

- 大力矩交流变频电机，无污染，延长使用寿命。
- 进口变频驱动系统，智能控制系统，保证工作平稳可靠。
- 设有超温、超速、电子门锁、不平衡等多种保护
- 智能界面，TFT真彩大屏幕触摸液晶显示、微机控制，同步显示设定参数和运行参数。
- 用户可设定16个运行程序，可随时修改运行转子的控制参数。
- 可编程操作，10档升降速时间供用户任意设定。
- 可显示转速上升、下降曲线、离心积分曲线、温度曲线。

Features

- AV motor of variable frequency and high torque, free from contamination caused by carbon dust, which helps to prolong the service life.
- Imported variable frequency drive system and automatic control system to ensure steady and reliable operation.
- Multiple protections such as overheat, hypervelocity, electronic locking, and imbalance.
- Intelligent interface featured by a TFT true-color LCD widescreen touch monitor, micro-computer control and simultaneous indication of both the set parameters and operation ones.
- With 16 operation programs to be set by the user and the control parameters of the rotor to be modified at any time.
- Operations can be programmed, 10 levels of speed-up and speed-down time limits for the user to choose freely.
- Can indicate the ascending and declining curves of the rotor, the centrifugal integral curves and the temperature curves.



技术参数 Specification

型号 Model	HR26M
最大容量 Max Capacity	4 × 1000ml
最高转速 Max Speed (r/min)	25000
最大离心力 Max RCF (×g)	64983
标配转子 Standard rotor	24 × 1.5/2.0ml
转速精度 Speed precision	± 50r/min
制冷系统 Refrigeration system	进口无氟制冷压缩机组和控制阀(R404a) Import fluoride-free compressor and control valve (R404a)
温控范围 Temp. control range	-20℃ ~ +40℃
温控精度 Temp. precision	± 1℃
定时范围 Timer range	0-99h59min
噪音 Noise	≤65dB
电源 Power	AC220V 50Hz
重量 Weight	260kg
外形尺寸 Dimension (L × W × H)	840 × 730 × 960mm

可选配件 Optional fittings



6 × 50ml

6 × 500ml

4 × 1000ml

产品名称 Model	容量 Capacity	最高转速 Speed (r/min)	最大离心力 RCF(×g)
角转子 Angle rotor	24 × 1.5/2.0ml	25000	64983
	18 × 10ml	23000	60460
	8 × 50ml	21000	52356
	4 × 250ml	15000	33800
	6 × 250ml	14000	30070
	6 × 500ml	10000	17700
	4 × 1000ml	8000	12040